

IMAGING SOLUTIONS

HealthIT

Products Selected Specifically for **Healthcare** Environments

HP DreamColor LP2480zx

GV546A8#ABA

General

DISPLAY TYPE: LCD display / TFT active matrix

BUILT-IN DEVICES: USB hub

WIDTH: 20.7 in

DEPTH: 10 in

HEIGHT: 22.2 in

WEIGHT: 27.6 lbs

ENCLOSURE COLOR: Silver, carbonite

LOCALIZATION: English / United States

Display

DIAGONAL SIZE: 24" - widescreen

VIEWABLE SIZE: 24"

DOT PITCH / PIXEL PITCH: 0.27 mm

MAX RESOLUTION: 1920 x 1200 / 60 Hz

MAX SYNC RATE (V X H): 75 Hz x 80 kHz

VIDEO BANDWIDTH: 200 MHz

RESPONSE TIME: 6 ms

TYPICAL RESPONSE TIME: 13 ms (rise+fall); 6 ms (gray-to-gray)

CONTROLS / ADJUSTMENTS: Brightness, H/V position, saturation, color temperature, clock, black level, hue

DISPLAY POSITIONS ADJUSTMENTS: Height, pivot (rotation), swivel, tilt

OSD LANGUAGES: Chinese (simplified), English, French, Italian, Spanish, Dutch, Japanese

DISPLAY SCREEN COATING: Anti-glare, anti-static

BACKLIGHT LIFE: 50,000 hour(s)

SIGNAL INPUT: HDMI, 2xDVI-I, DisplayPort

The HP DreamColor LP2480zx Professional Display is the world's only color-critical LCD based on HP DreamColor Engine technology. This uniquely affordable monitor delivers broad color support, rich visual quality, and consistent results.

This monitor comes standard with a 4-port integrated USB 2.0 hub – perfect for quick mouse & peripheral connections.

HealthDynamix Price: \$2,350.12*

* Pricing and terms subject to change without notice. Call for Special Pricing and/or Volume Discounts



Additional Product Specifications

IMAGE

Image Color Temperature: 6500K
Image Brightness: 250 cd/m2
Image Contrast Ratio: 1000:1
Image Max H-View Angle: 178
Image Max V-View Angle: 178

EXPANSION / CONNECTIVITY

Interfaces: 1 x USB upstream • 4 x USB downstream • 2 x DVI-I - 29 pin combined DVI • 1 x HDMI • 1 x DisplayPort • 1 x component video input • 1 x S-video input • 1 x composite video input

MISCELLANEOUS

Cables Included: 1 x DVI-VGA cable - VGA to DVI-I - 6.6 ft • 1 x DVI cable - DVI-D to DVI-I - 6.6 ft • 1 x display cable - 6.6 ft • 1 x HDMI cable - 6.6 ft • 1 x USB cable - 6.6 ft
Flat Panel Mount Interface: 100 x 100 mm
Features: Security lock slot (cable lock sold separately), wall mountable
Compatible with Windows 7
Compliant Standards: CE, CSA, TUV, VCCI, GS, ISO 13406-2, TCO '99, MIC, FCC, CISPR

POWER

Form Factor: Internal
Voltage Required: AC 120/230 V (50/60 Hz)
Power Consumption Operational: 42 Watt
Power Consumption Stand by / Sleep: 10 Watt
Software / System Requirements
Software Included: Drivers & Utilities, HP Display Assistant

MANUFACTURER WARRANTY

Service & Support: 3 years warranty
Service & Support Details:
Limited warranty - parts and labor - 3 years - on-site

ENVIRONMENTAL PARAMETERS

Min Operating Temperature: 41 °F
Max Operating Temperature: 95 °F
Humidity Range Operating: 20 - 80%

HIT Solutions for Your Specific Needs



Health Dynamix