

Products Selected Specifically for **Healthcare** Environments

HP LA1905wg LCD Monitor

NM360A8#ABA

General

DISPLAY TYPE: LCD display / TFT active matrix

TFT TECHNOLOGY: TN

BUILT-IN DEVICES: USB hub

WIDTH: 17.5 in

DEPTH: 9.6 in

HEIGHT: 14.6 in

WEIGHT: 13.7 lbs

LOCALIZATION: English / United States

Display

DIAGONAL SIZE:

19" - widescreen

VIEWABLE SIZE: 19"

DOT PITCH / PIXEL PITCH: 0.2835 mm

MAX RESOLUTION:

1440 x 900 / 60 Hz

MAX SYNC RATE (V X H):

76 Hz x 83 kHz

VIDEO BANDWIDTH: 140 MHz

RESPONSE TIME: 5 ms

CONTROLS / ADJUSTMENTS:

Brightness, contrast, H/V position, color temperature, phase, clock

DISPLAY POSITIONS ADJUSTMENTS:

Height, pivot (rotation), swivel, tilt

OSD LANGUAGES: Chinese

(traditional), Chinese

(simplified), English,

German, French, Italian,

Portuguese, Spanish,

Dutch, Japanese

BACKLIGHT LIFE: 50,000 hour(s)

TILT ANGLE: 35

SIGNAL INPUT: DVI-D,

VGA, DisplayPort

FEATURES: HDCP, 72% color gamut



Additional Product Specifications

IMAGE

Image Color Temperature: 9300K, adjustable, 6500K
Image Aspect Ratio: 16:10
Image Brightness: 250 cd/m2
Image Contrast Ratio: 1000:1 / 3000:1 (dynamic)
Image Max H-View Angle: 160
Image Max V-View Angle: 160

EXPANSION / CONNECTIVITY

Interfaces: 1 x DVI-D - 24 pin digital DVI ; 1 x VGA - 15 pin HD D-Sub (HD-15) ; 1 x DisplayPort - 20 pin DisplayPort ; 2 x USB downstream - 4 pin USB Type A ; 1 x USB upstream - 4 pin USB Type B

MISCELLANEOUS

Cables Included: 1 x USB cable - 1 x VGA cable - 6 ft - 1 x DVI cable - 6 ft
Flat Panel Mount Interface: 100 x 100 mm
Compatible with Windows 7
Compliant Standards: Plug and Play, CE, TUV, VCCI, BSMI CNS 13438 Class B, cUL, GS, EN55022 Class B, FCC Part 15 B, CCC, EN55024 Class B, UL 60950-1, IEC 60950-1, EN 60950-1, CSA C22.2 No. 60950-1-03, TCO Displays 5.0, ISO 9241-307, KCC, CISPR, GEEA, AS/NZS 3548 Class B

POWER

Form Factor: Internal
Voltage Required: AC 120/230 V (50/60 Hz)
Power Consumption Operational: 33 Watt
Power Consumption Stand by / Sleep: 2 Watt

ENVIRONMENTAL STANDARDS

EPEAT Compliant: EPEAT Gold
ENERGY STAR Qualified: Yes

ENVIRONMENTAL PARAMETERS

Min Operating Temperature: 41 °F
Max Operating Temperature: 95 °F
Humidity Range Operating: 20 - 80%

Achieve your business goals with the comfort-focused, energy-efficient and kind to the environment HP Compaq LA1905wg 19-inch widescreen LCD monitor.

Selected by HP as a unit ideal for healthcare, this monitor can serve at both the nurses' station or for cart/mobile unit installations. The LA1905wg comes standard with two USB ports for quick connection of a wired mouse or peripheral.

HealthDynamix Price: \$185.44*

** Pricing and terms subject to change without notice
Call for Special Pricing and/or Volume Discounts*

HIT Solutions for Your Specific Needs

